

SPECIFICATIONS

- CURB W/INTEGRAL CAPFLASHING 3mm ALUMINIUM (CORNERS FULLY WELDED)
- 2. COVER 3mm ALUMINIUM
- 3. COVER LINER 1mm ALUMINIUM
- 4. 50MM POLYISOCYANURATE CURB INSULATION
- 5. 50MM POLYISOCYANURATE COVER INSULATION
- 6. EPDM GASKET (ALL AROUND COVER)
- 7. PINTLE HINGE STAINLESS STEEL TYPE 316
- 8. Bilclip® FLASHING SYSTEM
- 9. ACTUATOR WITH CARRIAGE 24VDC (SEE NOTE 1)
- 10. JUNCTION BOX
- 11. WIND DEFLECTOR 4mm ALUMINUM

SHOP FINISH

ALUMINIUM: MILL FINISH

HARDWARE: CORROSION RESISTANT (UNLESS OTHERWISE SPECIFIED)

NOTES:

- 1. THE TRAVEL OF THE ACTUATOR WILL PASS BELOW THE BASE MOUNTING FLANGE POSITION. ENSURE THERE ARE NO OBSRUCTIONS BELOW.
- THIS PRODUCT IS DESIGNED TO BE INSTALLED ON A FLAT ROOF.
- FULL SPECIFICATIONS ARE AVAILABLE ON WEBSITE: www.bilcouk.co.uk

CUSTOMER

P.O. NO.

JOB

SALES REP.



Bilco UK Ltd, Pavilion 7 Fornham Business Court Hall Farm, Fornham St. Martin Bury St. Edmunds, Suffolk, IP31 1SL

SINGLE LEAF SMOKE VENT TYPE ESS-50REM

QTY	TYPE	SIZE WIDTH X LENGTH
	ESS-50REM	Х

Web Site: www.bilcouk.co.uk

HINGE SIDE